Expert Solutions in Seal-less Hygienic Transfer





Where Innovation Flows

ECCENTRIC DISC PUMPS



mouvex.com



Gentle. Clean. Consistent. Mouvex Eccentric Disc Technology is the **Solution for Your Dairy Product Production Process**

Dairy Product Manufacturing Challenges:

Dairy product manufacturers face the following challenges in their day-to-day operations:

- Preservation of final product quality
- Having the cleanest operating conditions
- Minimizing product loss and recovering ingredients
- Handing extremely shear sensitive products and ingredients



Yogurt culture injection

- Low shear (fragile product)
- Constant flow rate vs. variable pressure

Pumps used throughout each phase of all kinds of dairy product production processes must have the following attributes to meet those challenges:

- Gentle product handing
- Perfect cleanability .
- Volumetric consistency
- Able to recover expensive products and ingredients



Flavored milk dosing

- Constant flow rate vs. variable pressure
- Non pulsating flow
- Product recovery



Rework process Constant flow rate vs.

- variable viscosity
- Product recovery





Aerating system feeding

 Constant flow rate vs. variable pressure Low shear



variable pressure Non pulsating flow

Constant flow rate vs.

Heat exchanger feeding

- Constant flow rate through heat exchanger.
- Vacuum to prime with a viscous cream
- Product recovery



Mouvex Eccentric Disc Pumps: The Solution for the Challenges of Dairy Production

- Low shear due to eccentric disc technology and lack of mechanical seal and bushings
- Consistent performance (flow, pressure and volumetric efficiency) thanks to low slippage.
- Product recovery (pipeline stripping), means profit recovery
- Non-pulsating, smooth flow
- Self-priming to take ingredients from drums
- · Easy to maintain: no seals, no metal/elastomer friction, only two pumping parts
- High volumetric efficiency allowing accurate formulation
- Clean-in-Place (CIP) capable for the ultimate in convenience and cleanliness
- Unique seal-less design eliminates leakage





Micro C Series The seal-less pump for small flow rates. Up to 800 l/hr (3.5 gpm)

S Series The seal-less pump with quick dismantling for daily hand cleaning. Up to 12 m³/hr (52 gpm)



Mouvex Technology

SLS Series The CIP capable seal-less pump for various applications. Up to 36 m³/hr (158 gpm)

Eccentric disc pumps consist of a cylinder and pumping element mounted on an eccentric shaft. As the eccentric shaft is rotated, the pumping element forms chambers within the cylinder, which increase in size at the intake port, drawing fluid into the pumping chamber. The fluid is transported to the discharge port where the pumping chamber size is decreased. This action squeezes the fluid out into the discharge piping.

Mouvex Principle





Where Innovation Flows



ZI la Plaine des Isles • 2 rue des Caillottes F-89000 AUXERRE - FRANCE T: + 33.3.86.49.86.30 F: + 33.3.86.46.42.10 contact@mouvex.com mouvex.com

Authorized PSG Partner:

ed in this d